


# Emergency hatches with coaming

### Purpose

Hatches for leisure boats, professional vessels and other sectors such as wind power



#### Characteristics

Flush hatches or with coaming under customer demand, built with the customer's own standards or customized design complying with applicable rules and regulations (ns 6028, une en-iso 12216, reglamentos...).

### **Lock System**

Centralized closure

#### **Materials**

Steel Stainless steel Aluminium

#### **Accessories**


Gas spring
Counterweight
Spring
Insulation
Inner lock
Ask for more options




## Technical specification Emergency hatches with coaming

| 1 | Max. Dimensions            | Upon request    | -                             | -         |
|---|----------------------------|-----------------|-------------------------------|-----------|
| 2 | Coaming material           | Steel           | Stainless Steel               | Aluminium |
| 3 | Coaming profile            | Flat Bar        | Angled Bar                    | -         |
| 4 | Door leaf material         | Steel           | Stainless Steel               | Aluminium |
| 5 | Opening mechanism material | Stainless Steel | -                             | -         |
| 6 | Type of opening            | Hinged          | Counterweight - Gas Spring    | Spring    |
| 7 | Hinges qty                 | 2               | -                             | -         |
| 8 | Insulation                 | None            | Rockwool                      | -         |
| 9 | Surface treatment          | Painting        | Sandblasting + primer coating | _         |
|   |                            |                 |                               |           |

#### Details:





Opening Dimensions

